



Quick Inflation and Deflation



Rubber Material Choice



STAINLESS STEEL



Manufactured with
3 Times Safety
Factor



600 - 2000 mm
24" - 80"



- 40 / +115 °C

PILLOW PACKER

Part Number	Nominal Size	Min.Pipe Dia. Ø (mm)	Product Width (mm)	Product Length (mm)	Required Inflation Pressure (Bar)	Type of Quick Inflation	Repair Lengths at Max.Dia.(mm)	Product Weight (kg)
PP6001000-25	600-1000	600	910	2500	1	1/4" quick coup.+ 1" Storz	1000	23
PP6001000-35	600-1000	600	910	3500	1	1/4" quick coup.+ 1" Storz	2000	32
PP8001200-25	800-1200	800	1200	2500	1	1/4" quick coup.+ 1" Storz	1000	38
PP8001200-35	800-1200	800	1200	3500	1	1/4" quick coup.+ 1" Storz	2000	42
PP10001400-25	1000-1400	1000	1550	2500	0,8	1/4" quick coup.+ 1" Storz	1000	45
PP10001400-35	1000-1400	1200	1550	3500	0,8	1/4" quick coup.+ 1" Storz	2000	55
PP12001600-25	1200-1600	1200	1800	2500	0,6	1/4" quick coup.+ 1" Storz	1000	65
PP12001600-35	1200-1600	1200	1800	3500	0,6	1/4" quick coup.+ 1" Storz	2000	75
PP15002000-28	1500-2000	1500	2300	2800	0,5	1/4" quick coup.+ 1" Storz	1000	95
PP15002000-37	1500-2000	1500	2300	3700	0,5	1/4" quick coup.+ 1" Storz	2000	110

